


Servo Drive CLDP Technical Data Sheet



Design and Function

CLDP (Closed Loop Differential Pump) is a hydraulic linear axis suitable for all applications with high density and high dynamics. Consisting of a servo motor, internal gear pump and a directly linked hydraulic cylinder, CLDP is a compact and closed system.

The integrated servo pump is matched to the surface area ratio of the cylinder. Speed and direction of movement is controlled without any directional or proportional valves. Because of the closed loop system, CLDP does not need a tank or

external power pack. The necessary volume compensator is integrated.

Position control and pressure/force control is possible. The pressure transducer is integrated into the system (option). An integrated position feedback sensor is available. Key features of CLDP are very high energy efficiency and virtually wearless operation. Hydraulic's intrinsically good overload protection is combined with long life time.

Technical Data

Ambient temperature	-5°C to +40°C
Mounting position	any
Working force	up to 500 kN
Stroke length	50, 100, 200, 300, 400 mm
Linear feedback system (option)	absolute encoder
Position accuracy	0.01 mm
Pressure accuracy	0.5% FS (full scale)
Repeatability	0.01 mm
IP rating	IP54 / IP64
Control	position and/or pressure control
Service interval	3 years or 20,000 operating hours

Scope of Delivery

Basic version:

- complete drive unit:
 - motor, pump, cylinder, compensation tank, valves, pressure switch
 - oil filling with high performance fluid PF-700
 - drift protection (not a safety component)


Options:

- pressure transducer
- servo converter with safety relay and interface cards (e.g. analog, CANopen, Ethernet, ...)
- line filter, mains line choke, brake resistor
- motor cable, encoder cable
- parameterization software
- start-up on-site
- integrated position feedback sensor (absolute)

Applications

- bending machines
- cutting machines
- forming machines
- presses
- special machines
- general replacement of spindle drives with servo motor
- material handling
- testing machines (laboratory)
- food industry

System Drawing




Data Standard Sizes

	CLDP 10	CLDP 20	CLDP 40
force [kN]			
speed [mm/s]			
25	430	550	640
50	275	550	640
75	175	350	640
100	105	215	400
125	105	215	400
150	70	140	255
175	70	140	255
200	70	140	255
225	-	95	175
250	-	95	175
275	-	95	175
300	-	95	175
350	-	-	130
400	-	-	130
450	-	-	100
500	-	-	100

additional data on request

Design




- 1 linear
- 2 parallel (option)
- 3 orthogonal (option)

movement direction of the piston rod →


Product Characteristics

Characteristics	Advantages	Benefits
<ul style="list-style-type: none"> • Servo drive with hydraulic power transmission 	<ul style="list-style-type: none"> • The drive is wear-resistant and absolutely overload-safe <hr/> <ul style="list-style-type: none"> • The drive has only a few electrical interfaces 	<ul style="list-style-type: none"> + Your drive components and moving parts have a long lifetime + After an overload occurs, your machine or equipment can be quickly and easily restarted <hr/> <ul style="list-style-type: none"> + This keeps your startup effort and costs low + No staff with knowledge of hydraulics is required
<ul style="list-style-type: none"> • Closed-loop hydraulic system with no directional control valves or servo valves 	<ul style="list-style-type: none"> • The integrated hydraulic system is a stand-alone system (self-contained) 	<ul style="list-style-type: none"> + You save the procurement and maintenance costs required for an external hydraulic power pack with all of its piping and tubing + The linear drive is easy and cost-effective to install in machines and equipment
<ul style="list-style-type: none"> • The hydraulic cylinder is controlled with a servo pump whose flow rate is matched to the cylinder surfaces 	<ul style="list-style-type: none"> • Simple and compact design with no classic valve and control technology <hr/> <ul style="list-style-type: none"> • Hydraulic system throttle losses are kept to a minimum 	<ul style="list-style-type: none"> + The linear drive requires up to 50% less energy, reducing your operational costs + The costs for commissioning, training, and maintenance are low <hr/> <ul style="list-style-type: none"> + The drive is energy-efficient and has low cooling requirements
<ul style="list-style-type: none"> • Standardized linear drive with very few components and modular design 	<ul style="list-style-type: none"> • This keeps planning costs associated with system integration low • A large number of designs and sizes are available 	<ul style="list-style-type: none"> + This reduces development times and development costs associated with your machinery or equipment


Control Principle: Speed and Pressure Control Integrated in the Servo Converter




Control Principle: Speed, Position and Pressure Controller Integrated in the Servo Converter




Control Principle: Motion Block Control Integrated in the Servo Converter






all dimensions in mm
 all dimensions for reference only
 * depending on version
 ** plug position may be rotated in 90° steps

force [kN]	\varnothing piston	$\varnothing D$	A	C	M	g2	B	E	SW
25	40	40f7	235	255	M16x1	4x M20	150	110	25
50	50	50f7	235	255	M20x1,5	4x M20	150	110	30
75	63	63f7	235	255	M30x2	4x M20	150	110	41
125	80	80f7	250	270	M36x2	4x M20	150	110	50
200	100	100f7	255	280	M42x2	4x M20	160	110	65
300	120	120f7	265	290	M48x2	4x M24	180	130	75



all dimensions in mm
 all dimensions for reference only
 * depending on version
 ** plug position may be rotated in 90° steps

force [kN]	Ø piston	Ø D	A	C	M	g2	B	E	SW
50	50	50f7	235	255	M20x1,5	4x M20	150	110	30
75	63	63f7	235	255	M30x2	4x M20	150	110	41
125	80	80f7	250	270	M36x2	4x M20	150	110	50
200	100	100f7	255	280	M42x2	4x M20	160	110	65
300	120	120f7	265	290	M48x2	4x M24	180	130	75
400	140	140f7	285	310	M64x2	4xM30	210	160	90



force [kN]	Ø piston	Ø D	A	C	M	g2	B	E	F	SW
75	63	63f7	235	255	M30x2	4x M20	150	110	-	41
125	80	80f7	250	270	M36x2	4x M20	150	110	-	50
200	100	100f7	255	280	M42x2	4x M20	160	110	-	65
300	120	120f7	265	290	M48x2	4x M24	180	130	-	75
400	140	140f7	285	310	M64x2	4x M30	210	160	-	90
500	160	160f7	305	330	M64x2	4x M30	240	180	-	100

Performance Fluid PF-700 for Servodrive CLDP

Performance Fluid PF-700 was developed especially for all power transmission systems with special requirements on tribology, temperature, oxidation and shearing stability. The result is a very high application period at minimum degradation.


- very low frictional losses, therefore significantly enhanced efficiency of power transmission
- energy saving
- high viscosity index
- outstanding wear protection characteristics
- compatible with commonly used sealing materials

For the servo drive CLDP, exclusive use of PF-700 is mandatory.

Further data: 25000864510-TED-ENX- and 25000864610-DSH-ENX-.

www.Laheghi.com

Type Code



www.Laheghi.com

Voith Turbo H + L Hydraulic GmbH & Co. KG
Schuckertstr. 15
71277 Rutesheim, Germany
Tel. +49 7152 992-3
Fax +49 7152 992-400
sales-rut@voith.com
www.voith.com/hydraulic-systems



VOITH
Engineered Reliability