


S1095 Series (NC,3/2 Way) High Pressure Solenoid Valve



S1095 series are high pressure solenoid valves. S1095 series are NC and 3/2 Way.

Application: Compressor, High pressure systems


Coils: 12V, 24V, 48V, 110V, 230V AC
12V, 24V, 48V, 110V DC

On request: Exproof models.

De energized:

1: Close


From 2 to 3: Open



Energized:

From 1 to 2: Open

3: Close



Materials

Diaphragm	NBR (On request Viton, EPDM)
Core	Stainless Stain
Tube	Stainless Stain
Body	Brass
Fluid	Air, Water, Gas etc.

Technical Features

Model	Connection Size	Orifice	Pressure		Temperature	Kv	Diaphragm
			Min	Max			
	G	mm			°C	Lit/min	
S1095.00.010	1/8"	1	0	16	-10°C...80 °C	0,6	NBR
S1095.00.018	1/8"	1,8	0	10	-10°C...80 °C	1,6	NBR
S1095.00.025	1/8"	2,5	0	7	-10°C...80 °C	3,2	NBR
S1095.01.010	1/4"	1	0	16	-10°C...80 °C	0,6	NBR
S1095.01.018	1/4"	1,8	0	70	-10°C...80 °C	1,6	NBR
S1095.01.025	1/4"	2,5	0	7	-10°C...80 °C	3,2	NBR

SMS Sanayi Malzemeleri Üretim ve Satış A.Ş.

Merkez : Bostancı Yolu Cad. Kuru Sok. No:16 Y. Dudullu, 34776 Ümraniye / İstanbul - Türkiye
Tel: +90 (216) 364 34 05 (pbx) Fax: +90 (216) 364 37 57

Fabrika: Çerkeşli OSB Mah. Dilovası İMES OSB 5.Cad. No:6 - Kocaeli / Türkiye
Tel: +90 (262) 290 20 20 Fax: +90 (262) 290 20 21