

Group Solenoid Valves S8210 Series (G1/8", G1/4")

GENERAL FEATURES

- TORK series S8210 direct acting group solenoid valves are 2/2 way normally closed
- Suitable for non-aggressive liquids (water, light oil (2E) etc...), gaseous fluids (air, inert gases etc...)
- Working Temperature: -10 °C/ +80 °C
- Don't require any differential pressure
- High reliability, quality and performance; long life, corrosion resistance.
- Wide pressure ratings, range of flow rate and orifice options.
- Ideal for the automatic control of media in a wide range of applications.
- On request; 1,8 - 3- and 4 mm orifice and high flow rate
- TORK solenoid valves satisfy relevant 97/23/EC, Pressure Equipment Directive (PED) and 2006/95/EEC Low Voltage Directive (LVD).
- Coils interchangeable
- Solenoid valves must be used with filtered fluids.
- Solenoid valve can be mounted in any position without affecting operation; vertical with coil upwards preferred.
- Standard pipe connection is G (BSP) (ISO 228-1) and on request; other pipe connections are available (NPT (ANSI 1.20.3))

ELECTRICAL CHARACTERISTICS

Continuous Duty	: ED %100
Coil Insulation Class	: H (180°C)
Coil Impregnation	: Polyester Fiber Glass
Coil Encapsulation Material	: Fiber Glass Reinforced
Ambient Temperature	: from -10°C, +60°C
Protection Degree	: IP65 (ISO 60529) with coil duly fitted with the plug connector
Electric Plug Connection	: DIN 46340 3 – Poles Connector (DIN43650)
Connector Specification	: ISO 4400 / EN 175301-803 Form A, Spade Plug (Cable Ø6-8 mm)
Electrical Safety	: IEC 335
Standard Voltages	: For AC 12V, 24V, 48V, 110V, 230V For DC 12V, 24V, 48V, 110 V

On request other voltages
 Voltages Tolerance : For AC -15%; +10%, For DC -5%; +10%
 Frequency : 50Hz/60Hz
 On request; connector with LED
 Specify coil volt age with order

MATERIALS IN CONTACT WITH FLUID

Body : Brass
 Internal Parts : Stainless Steel
 Sealing : NBR
 Shading Ring : Copper
 Seats : Stainless Steel
 Core Tube : Stainless Steel
 Springs : Stainless Steel
 On request; nickel plated body
 On request; sealing can be FPM (VITON), EPDM

TECHNICAL FEATURES

Max. Viscosity : 5°E (-37cST or mm²/s)
 Response Time : Opening time : 30 ms
 Closing Time : 30 ms

Code Explain: S8210.00.025 - 2 - 1



SEALS FEATURES

NBR : -10°C...+80°C
 EPDM : -10°C...+130°C
 VITON : -10°C...+160°C
 PTFE : -10°C...+180°C
 RUBY : -10°C...+160°C

NORMALLY CLOSED


2/2 WAY

DIRECT OPERATED

ΔP=0



Dimensions (mm)					
G	A	B	C	D	E
1/8"	125	85	40	77	6.2
1/4"	125	85	40	77	6.2



Coils	Nominal Values	Cold/Hot	Inrush	Holding	Current (A)	Surface Temperature (°C)
C40012VDC18W	12VDC 18W	COLD	19,56	19,56	1,63	20
		HOT	14,52	14,52	1,21	106
C40024VDC18W	24VDC 18W	COLD	20,88	20,88	0,87	25
		HOT	14,64	14,64	0,61	116
C40110VDC18W	110VDC 18W	COLD	19,96	19,96	0,18	23
		HOT	13,56	13,56	0,123	115
C40012VAC15VA	12VAC 15VA	COLD	23,81	16,43	1,3	25
		HOT	-	15,86	1,262	79
C40024VAC15VA	24VAC 15VA	COLD	25,82	15,02	0,62	22
		HOT	-	13,91	0,57	81
C40110VAC15VA	110VAC 15VA	COLD	30,65	15,17	0,137	24
		HOT	-	13,96	0,126	80
C40230VAC15VA	230VAC 15VA	COLD	31,4	15,64	0,068	25
		HOT	-	14,41	0,063	80
C40230VAC15VA	230VAC 24VA	COLD	45,1	23,92	0,0154	23
		HOT	-	21,62	0,0154	100

Valve Type/ Order No	Connection Size	Orifis Ölçüsü	Pressure min/max		Kv	Fluid Temperature		Seal			Weight
			Bar	Bar		°C		NBR	Opsiyon		
S8210	G	mm	Bar	Bar	Lt/dk	min	max		Viton	EPDM	kg
S 8210.00.025.12	1/8"	2.5	0	12	2.8	-10	80	✓	✓	✓	1.05
S 8210.00.025.13	1/8"	2.5	0	12	2.8	-10	80	✓	✓	✓	1.55
S 8210.00.025.14	1/8"	2.5	0	12	2.8	-10	80	✓	✓	✓	2.05
S 8210.00.025.21	1/8"	2.5	0	12	2.8	-10	80	✓	✓	✓	0.87
S 8210.00.025.31	1/8"	2.5	0	12	2.8	-10	80	✓	✓	✓	1.25
S 8210.00.025.41	1/8"	2.5	0	12	2.8	-10	80	✓	✓	✓	1.48
S 8210.01.025.12	1/4"	2.5	0	12	2.8	-10	80	✓	✓	✓	0.95
S 8210.01.025.13	1/4"	2.5	0	12	2.8	-10	80	✓	✓	✓	1.45
S 8210.01.025.14	1/4"	2.5	0	12	2.8	-10	80	✓	✓	✓	1.95
S 8210.01.025.21	1/4"	2.5	0	12	2.8	-10	80	✓	✓	✓	0.77
S 8210.01.025.31	1/4"	2.5	0	12	2.8	-10	80	✓	✓	✓	1.15
S 8210.01.025.41	1/4"	2.5	0	12	2.8	-10	80	✓	✓	✓	1.38