




Normally Closed



- Tork series, S8450 direct operation solenoid valves are manufactured 1/4", 3/8", 1/2" and 3/4" in dimensions, are 2/2 way normally closed.
- Isolation solenoid valves are preferred where corrosive fluids are used.
- Applications are chemical processes, analysis equipment, water treatment and drip irrigation systems etc.

Technical Specifications

Body: PVC

Tube and internal parts: Stainless Steel

Ambient Temperature: -10 ° C... +60 ° C

Diaphragm Temperature: -10 ° C... +80 ° C (Viton)

Coils: 12VDC, 24VDC, 48VDC, 110VDC

12VAC, 24VAC, 48VAC, 110VAC, 230VAC

Protection Class: IP 65,

On request; IP68

Valve Type/ Order No	Connection Size	Orifice Size	Pressure min/max		Kv lt/min	Fluid Temperature min / max		Diaphragm	Weight kg
			bar	bar		°C			
S845001030	1/4"	3	-1	6	3,1	-10	80	Viton	0,312
S845001040	1/4"	4	-1	4	4,4	-10	80	Viton	0,311
S845002040	3/8"	4	-1	4	4,2	-10	80	Viton	0,306
S845002070	3/8"	7	-1	1,5	9,4	-10	80	Viton	0,303
S845003070	1/2"	7	-1	1,5	9,1	-10	80	Viton	0,312
S845004070	3/4"	7	-1	1	8,9	-10	80	Viton	0,330