

# **PNEUMATIC ACTUATED PVC BALL VALVE**



## **Pneumatic Actuated PVC Ball Valve**

PVC ball valves can be controlled by pneumatic and electric actuator. PVC ball valves are suitable for water, acid and chemical fluid types. There are flanged , gear and slip types of connections.

## Benefits

- 1. Suitable for drinking water, asic and chemical fluids standards
- 2. Lower torque requirement for on-off
- 3. %100 running test at factory
- 4. Electric actuators suitability
- 5. Easy installation, de-installation possibilities

## Applications

- 1. Material : PVC
- 2. Size: 1/2" − 2 1/2"
- 3. Connection: threaded flanged- slip types
- 4. Working Pressure: 0-16 bar
- 5. Ambient Temperature: 0°C 50°C
- 6. Actuator Pressure: 4 8 bar
- 7. Standard: ISO 5211

## Featur s


- 8. It controls the water in the system. There are options with electric and pneumatic actuator.
- 9. It is acid resistance is aplified with its private sphere seal assembly. PVC and EPDM is used for control of the system to fit every kind of acid.
- 10. VITON seals use for the application where EPDM is not suitable. It has a high acid resistance.

HEAD OFFICE Y. Dudullu, Bostancı Yolu, Kuru Sok, No16 Ümraniye 34776 İstanbul - TURKEY P +9

P +90 216 364 34 05
F +90 216 364 37 57
P +90 262 290 20 20
F +90 262 290 20 21









- 1. Union Nut: PVC-PP-HDPE
- 2. End Connector: PVC-PP-HDPE
- 3. Body Seal: EPDM-Viton
- 4. **Body:** PVC-PP-HDPE
- 5. Backing Seal: EPDM-Viton
- 6. Ball Seal: PE-PP-Teflon
- 7. Ball: PVC-PP-HDPE

- 8. Carrier O-Ring: EPDM-Viton
- 9. Carrier Ball: PVC-PP-HDPE
- 10. Seat Carriet: PVC-PP-HDPE
- 11. Valve Handle: ABS
- 12. Handle Cover: PVC
- 13. Step: PVC-PP-HDPE
- 14. Step Seal: EPDM- Viton





ACT. TYPE	DN	Α	в	С	D	Е	F
DA 40	15	139,2	70,6	114	45	70	150,5
DA 40	20	139,2	70,6	135	55	70	160
DA 40	25	139,2	70,6	149	66	70	169
DA 40	32	139,2	70,6	168	82	70	178
DA 40	40	139,2	70,6	175	98	70	197
DA 60	50	178	82,5	208	120	85	223

ACT. TYPE	DN	Α	В	С	D	Е	F
SR 40	15	139,2	70,6	114	45	70	150,5
SR 40	20	139,2	70,6	135	55	70	160
SR 40	25	139,2	70,6	149	66	70	169
SR 60	32	139,2	70,6	168	82	70	193
SR. 60	40	139,2	70,6	175	98	70	212
SR 80	50	178	82,5	208	120	85	255

#### Double Acting Pneumatic Actuated PVC Ball Valve

#### Spring Return Pneumatic Actuated PVC Ball Valve

HEAD OFFICE

Y. Dudullu, Bostancı Yolu, Kuru Sok, No16 Ümraniye 34776 İstanbul - TURKEY İMES O.S.B. 5. Cadde No6 Çerkeşli O.S.B. Mahallesi Dilovası Kocaeli - TURKEY P +90 216 364 34 05
F +90 216 364 37 57
P +90 262 290 20 20
F +90 262 290 20 21

www.smstork.com